



SIZE	INLET										OUTLET									
	D	A	B	C	E	F	G	H	J	K	L	M	N	P	Q	R	S	T	U	V
12	73	-	-	18	8 ^{1/2}	16	4	25	-	12	14	6	13	12	16	7 ^{1/2}	16	24	67	
16	95	-	-	22 ^{1/2}	11 ^{1/4}	19	4	33	-	18	18	8	16	16	20	10	20 ^{3/4}	30 ^{1/4}	73	
20	117	-	-	27	13 ^{3/4}	25	4	41	-	24	23	10	18	20	26	12	26 ^{1/4}	38 ^{3/4}	82	
24	140	-	-	32	16 ^{1/2}	29	6	49	-	29	27	12	21	24	31	15	31 ^{1/4}	45 ^{3/4}	91	
26	151	-	-	34	17 ^{3/4}	32	6	53	-	32	30	13	23	26	34	16	34	50	95	
28	162	-	-	36	19	34	6	57	-	35	32	14	24	28	37	17	36 ^{1/2}	53 ^{1/2}	98	
30	174	-	-	38	20 ^{3/4}	37	6	61	-	38	34	15	26	30	42	18	39 ^{1/4}	57 ^{3/4}	103	
32	185	-	-	40	22 ^{1/4}	39	6	65	-	41	36	16	27	32	42	20	41 ^{3/4}	61 ^{1/4}	106	
34	196	-	-	43	23 ^{1/4}	42	8	69	-	43	38	17	29	34	45	21	44 ^{1/2}	65 ^{1/2}	112	
36	209	-	-	45	24 ^{3/4}	45	8	73	-	47	41	18	31	36	48	22	47 ^{1/4}	69 ^{3/4}	117	
38	221	-	-	47	26 ^{1/4}	47	8	77	-	50	43	19	33	38	53	23	49 ^{3/4}	73 ^{1/4}	120	
40	232	-	-	49	27 ^{1/2}	49	8	81	-	53	45	20	34	40	54	24	52 ^{1/4}	76 ^{3/4}	124	
42	242	-	-	52	28 ^{3/4}	51	8	85	-	55	47	21	35	42	55	26	54 ^{3/4}	80 ^{1/4}	127	
45	259	-	-	59	30 ^{3/4}	55	10	90	-	60	51	23	37	46	60	28	58 ^{3/4}	86 ^{1/4}	135	
48	277	-	-	58	32 ^{3/4}	59	10	96	-	65	54	24	40	48	63	30	62 ^{3/4}	92 ^{1/4}	140	
51	293	-	-	61	35	62	10	102	-	69	57	26	42	50	69	31	66 ^{1/2}	97 ^{1/2}	146	
54	310	-	-	64	37 ^{1/4}	66	12	108	-	74	61	27	44	54	73	33	70 ^{1/2}	103 ^{1/2}	154	
57	284	110	38	67	39 ^{1/4}	69	12	-	71	79	64	29	46	58	75	35	74 ^{1/4}	108 ^{3/4}	-	
60	301	116	40	71	41 ^{1/4}	73	12	-	75	84	67	30	49	60	80	37	78 ^{1/4}	114 ^{3/4}	-	
64	317	124	42	74	43 ^{3/4}	78	14	-	80	89	72	32	51	64	84	40	83 ^{1/2}	122 ^{1/2}	-	
68	337	132	45	78	46 ^{3/4}	83	14	-	85	95	76	34	54	68	91	42	88 ^{3/4}	130 ^{1/4}	-	
72	356	138	47	82	49 ^{1/4}	87	14	-	90	101	81	36	57	72	96	44	93 ^{3/4}	137 ^{1/4}	-	
76	377	146	50	87	52	92	16	-	95	107	85	38	60	76	100	47	99	145	-	
80	397	156	52	91	54 ^{3/4}	97	16	-	100	114	90	40	63	80	107	49	104 ^{1/4}	152 ^{3/4}	-	
85	420	166	56	96 ^{1/2}	57 ^{1/4}	105	18	-	105	121	95	43	66	85	114	52	111 ^{1/4}	163 ^{3/4}	-	
90	445	174	59	101 ^{1/4}	61 ^{1/2}	109	18	-	112	129	101	45	70	90	120	55	117 ^{1/4}	171 ^{3/4}	-	
95	468	184	62	106	64 ^{3/4}	115	20	-	118	137	107	48	73	95	127	58	123 ^{3/4}	181 ^{1/4}	-	
100	492	194	65	111	68 ^{1/4}	121	20	-	124	145	113	50	76	100	134	61	130 ^{1/4}	190 ^{3/4}	-	
105	517	202	69	116	72	127	22	-	130	153	118	53	80	105	142	64	136 ^{3/4}	200 ^{1/4}	-	
110	541	212	72	121	75 ^{1/4}	133	22	-	136	160	124	55	84	110	149	67	143 ^{1/4}	209 ^{3/4}	-	
115	568	222	75	126	79	139	24	-	143	169	129	58	88	115	156	70	149 ^{3/4}	219 ^{1/4}	-	
120	593	232	78	131	82 ^{1/4}	146	24	-	150	177	135	60	91	120	161	74	156 ^{1/2}	229 ^{1/2}	-	

- Cyclone outlet orientation shown is standard. Optional orientations @ 3 o'clock, 6 o'clock and 9 o'clock are available.
- Dimensions shown are in inches, and are approximate. Request certified drawing for construction.
- Sizes 12 thru 54 are supplied with round Conical Single Hopper. Size 57 thru 120 with Twin Individual Hoppers, to suit shipping limitations.
- Dipleg and/or airlock are required for efficient operation.
- Contact our Engineering Dept. for any assistance.